Project Information

Building type Ground-floor maisonette

Reference	
Date	11 September 2019
Project	TYPE1_2BEDTH_SE_BeLean
-	Cardinal Court
	Woking
	GU22

REGULATION COMPLIANCE REPORT - Approved Document L1A, 2012 Edition, England

assessed by program JPA Designer version 6.04a1, printed on 13/9/2019 at 11:25:54

New dwelling as designed

1 TER and DER Fuel for main heating system: Gas (mains) (fuel factor = 1.00) Target Carbon Dioxide Emission Rate Dwelling Carbon Dioxide Emission Rate Excess emissions = 1.32kg/m ² (8.4%)	TER = 15.62 DER = 16.93	Fail
1b TFEE and DFEE Target Fabric Energy Efficiency (TFEE) Dwelling Fabric Energy Efficiency (DFEE)	TFEE = 49.9 DFEE = 45.3	ОК

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

2b Fabric U-values				
	Element	Average	Highest	
	Wall	0.13 (max. 0.30)	0.13 (max. 0.70)	OK
	Floor	0.13 (max. 0.25)	0.13 (max. 0.70)	OK
	Roof	0.13 (max. 0.20)	0.13 (max. 0.35)	OK
	Openings	1.44 (max. 2.00)	1.60 (max. 3.30)	OK
		. ,	. ,	

3 Air permeability

Air permeability at 50 pascals: Maximum : 3.00 10.00 OK

JPA Designer Version 6.03x IES iSAP, SAP Version 9.92 Licensed to Elementa Consulting

C:\Users\YMachnouk\Desktop\EGLEY - SAP Calcs\EGLEY SAP.JDP

Approval of JPA Designer by BRE applies only to the software, data is not subject to quality control procedures, users are themselves responsible for the accuracy of the data. The results of the calculation should not be accepted without first checking the input data.

ors, mains gas		
e 4 of SAP document		
	Fail	
Minimum: 88.0%	Fail	
	OK	
Yes	OK	
es Compliance Guide" by the DCLG)		
	OK	
Cylinderstat - Yes	OK	
	OK	
No	OK	
Percentage of fixed lights with low-energy fittings: 100.0% Minimum: 75.0%	ОК	
Specific fan power : 0.66 Efficiency : 93.00		
Maximum : 1.5W/(litre/sec) and efficiency not less than 70%	OK	
	OK	
Not significant	OK	
-		
100.00		
Thermal mass parameter : 100.00 Overshading : Average or unknown (20-60 % sky blocked)		
Orientation : NorthWest		
8.00		
% of daylight hours		
	Independent timer for DHW - Yes No Percentage of fixed lights with low-energy fittings: 100.0% Minimum: 75.0% Specific fan power : 0.66 Efficiency : 93.00 Maximum : 1.5W/(litre/sec) and efficiency not less than 70% Not significant 100.00	

Walls U-value 0.13 W/m²K Design air permeability 3.0 m³/h.m²


JPA Designer Version 6.03x IES iSAP, SAP Version 9.92 Licensed to Elementa Consulting C:\Users\YMachnouk\Desktop\EGLEY - SAP Calcs\EGLEY SAP.JDP Approval of JPA Designer by BRE applies only to the software, data is not subject to quality control procedures, users are themselves responsible for the accuracy of the data. The results of the calculation should not be accepted without first checking the input data.

Predicted Energy Assessment


TYPE1_2BEDTH_SE_BeLean Cardinal Court Woking GU22 Dwelling type: Date of assessment: Produced by Total floor area: Ground-floor maisonette 13 September 2019 Elementa Consulting 125 m²

This is a Predicted Energy Assessment for a property which is not yet complete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, an Energy Performance Certificate is required providing information about the energy performance of the completed property.

Energy performance has been assessed using the SAP 2012 methodology and is rated in terms of the energy use per square metre of floor area, energy efficiency based on fuel costs and environmental impact based on carbon dioxide (CO_2) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.



The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO_2) emissions. The higher the rating the less impact it has on the environment.