Project Information

Building type Ground-floor maisonette

Reference	
Date	11 September 2019
Project	TYPE2B_4BEDTH_NW_BeGreen
-	Cardinal Court
	Woking
	GU22

REGULATION COMPLIANCE REPORT - Approved Document L1A, 2012 Edition, England

assessed by program JPA Designer version 6.04a1, printed on 13/9/2019 at 11:28:23

New dwelling as designed

1 TER and DER Fuel for main heating system: Standard tariff (fuel factor = 1.55) Target Carbon Dioxide Emission Rate Dwelling Carbon Dioxide Emission Rate	TER = 25.21 DER = 16.85	ОК
1b TFEE and DFEE Target Fabric Energy Efficiency (TFEE) Dwelling Fabric Energy Efficiency (DFEE)	TFEE = 61.0 DFEE = 53.0	ОК

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

2b Fabric U-values				
	Element	Average	Highest	
	Wall	0.13 (max. 0.30)	0.13 (max. 0.70)	OK
	Floor	0.13 (max. 0.25)	0.13 (max. 0.70)	OK
	Roof	0.13 (max. 0.20)	0.13 (max. 0.35)	OK
	Openings	1.44 (max. 2.00)	1.60 (max. 3.30)	OK
3 Air permeability				
	Air permeabili	ty at 50 pascals:	3.00	OK
	Maximum :		10.00	

4 Heating efficiency

Main heating system: Air source heat pump, radiators, electric Mitsubishi Ecodan 11.2 kW Source of efficiency: from boiler database Secondary heating system: None -

JPA Designer Version 6.03x IES iSAP, SAP Version 9.92 Licensed to Elementa Consulting C:\Users\YMachnouk\Desktop\EGLEY - SAP Calcs\EGLEY SAP.JDP

Approval of JPA Designer by BRE applies only to the software, data is not subject to quality control procedures, users are themselves responsible for the accuracy of the data. The results of the calculation should not be accepted without first checking the input data.

Page 1 of 3

5 Cylinder insulation

Hot water storage No cylinder

6 Controls (Also refer to "Domestic Building Ser Space heating controls Hot water controls	ervices Compliance Guide" by the DCLG) 2205 Programmer + at least 2 room thermostats No cylinder	
Boiler Interlock	No	OK
7 Low energy lights		
	Percentage of fixed lights with low-energy fittings: 100.0% Minimum: 75.0%	ОК
8 Mechanical ventilation		
	Specific fan power : 0.79 Efficiency : 92.00 Maximum : 1.5W/(litre/sec) and efficiency not less than 70%	ОК
9 Summertime temperature		
Overheating risk (Thames Valley):		OK
Based on:	Not significant	OK
	100.00	
Thermal mass parameter : Overshading :	Average or unknown (20-60 % sky blocked)	
Orientation : SouthEast	Average of unknown (20-00 % sky blocked)	
Ventilation rate :	8.00	
Blinds/curtains :		
None with blinds/shutters closed 0	00% of daylight hours	

Pitched roofs insulated between joists U-value 0.13 W/m²K Walls U-value 0.13 W/m²K Design air permeability 3.0 m³/h.m²


JPA Designer Version 6.03x IES iSAP, SAP Version 9.92 Licensed to Elementa Consulting C:\Users\YMachnouk\Desktop\EGLEY - SAP Calcs\EGLEY SAP.JDP Approval of JPA Designer by BRE applies only to the software, data is not subject to quality control procedures, users are themselves responsible for the accuracy of the data. The results of the calculation should not be accepted without first checking the input data.

TYPE2B_4BEDTH_NW_BeGreenDwelling type:Cardinal CourtDate of assessment:WokingProduced byGU22Total floor area:


Ground-floor maisonette 13 September 2019 Elementa Consulting 147 m²

This is a Predicted Energy Assessment for a property which is not yet complete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, an Energy Performance Certificate is required providing information about the energy performance of the completed property.

Energy performance has been assessed using the SAP 2012 methodology and is rated in terms of the energy use per square metre of floor area, energy efficiency based on fuel costs and environmental impact based on carbon dioxide (CO_2) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.



The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO_2) emissions. The higher the rating the less impact it has on the environment.